

Imagine.

 Roland®

CAMM-1 PRO

Sign Maker by Roland DG Corporation

GX-500/GX-400/GX-300



***Roland CAMM-1 PRO —
The Name That More Professionals Trust***

Performance and Versatility in One Easy-To-Use Device

CAMM-1 PRO GX-500/GX-400/GX-300 Features:

- Professional, easy-to-use vinyl cutters for signs, vehicle graphics, retail displays, and more
- Proven CAMM-1 technology and legendary Roland reliability
- Cutting speeds of up to 850mm (33") per second for maximum productivity
- Mechanical resolution of 0.0125mm/step (0.00049") guarantees precision results
- Impressive maximum down force of 350 grams for performance with even the thickest materials
- Includes Roland CutStudio*1, feature-rich design software developed for Roland vinyl cutters
- Automatic 4-point registration system*2 produces accurate contour cuts every time
- Easy connection to your computer through USB or serial ports
- Plug-in software for Adobe® Illustrator® and CorelDRAW®*3, for a seamless, consistent operating environment
- Accepts a broad range of materials from sand blast to window film



*1 Compatible with Windows® 98SE/Me/2000/XP and Windows Vista®. *2 This system is accessed through Roland CutStudio software and plug-in software for Adobe Illustrator.
*3 Plug-in software is compatible with Adobe Illustrator 9/10/CS/CS2/CS3 for Windows, CorelDRAW 10/11/12/X3 for Windows, and Adobe Illustrator 9/10/CS/CS2/CS3 for Macintosh.



Specifications	GX-500	GX-400	GX-300
Mechanism / Driving method	Friction feed / Digital control servo motor		
Maximum cutting area	Width: 1195 mm (47 in.) Length: 24998 mm (984-1/8 in.)	Width: 1000 mm (39 in.) Length: 24998 mm (984-1/8 in.)	Width: 737 mm (29 in.) Length: 24998 mm (984-1/8 in.)
Acceptable media widths	Min. 90 mm (3-1/2 in.) Max. 1372 mm (54 in.)	Min. 90 mm (3-1/2 in.) Max. 1178 mm (46 in.)	Min. 50 mm (2 in.)/Max. 915 mm (36 in.) (50 to 540 mm (2 in. to 21 in.), 582 to 915 mm (23 in. to 36 in.))
Width of material that can be cut off	0 to 1270 mm (0 in. to 50 in.)	0 to 1067 mm (0 in. to 42 in.)	0 to 812 mm (0 in. to 32 in.)
Tools	Special blade for CAMM-1 series		
Maximum cutting speed	During cutting: 850 mm/sec. (in all directions) During tool-up: 1202 mm/sec. (in 45° direction)		
Cutting speed / Blade force	10 to 850 mm/sec. (in increments of 10 mm/sec.) / 20 to 350 gf		
Mechanical resolution	0.0125 mm/step (0.000492 in./step)		
Software resolution	0.025 mm/step (0.000984 in./step)		
Distance accuracy (*1)	Error of less than ± 0.2% of distance traveled, or 0.1 mm (0.00394 in.), whichever is greater		
Repetition accuracy (*1) (*2) (*3)	0.1 mm or less		
Interface	Serial (RS-232C-compatible), USB (Rev 1.1)		
Replot memory	2 MB (buffer size: 8 MB)		
Power supply / Power consumption	AC 100V to 240V ± 10% 50/60 Hz 1.2A / Approx. 100W		AC 100V to 240V ± 10% 50/60 Hz 1.1A / Approx. 95W
Dimensions with stand	1602 mm (W) x 727 mm (D) x 1113 mm (H) (63-1/16 in. (W) x 28-5/8 in. (D) x 43-13/16 in. (H))	1407 mm (W) x 727 mm (D) x 1113 mm (H) (55-3/8 in. (W) x 28-5/8 in. (D) x 43-13/16 in. (H))	1144 mm (W) x 727 mm (D) x 1113 mm (H) (45-1/16 in. (W) x 28-5/8 in. (D) x 43-13/16 in. (H))
Weight with stand	55 kg (121.2 lb.)	51 kg (112.4 lb.)	44 kg (97 lb.)
Included items	Power cord, blade holder (XD-CH2), pin, blade, alignment tool, cable clamp, replacement blade for sheet cutter, USB cable, Roland software CD-ROM, setup guide, user's manual		

*1 According to material and cutting conditions as specified by Roland DG Corp. *2 Excluding stretching/contraction of the material
*3 Range for assured repetition accuracy: For materials with a width exceeding 610 mm (24 in.): Length 4,000 mm (157-7/16 in.) (GX-500/400 only) . For materials with a width of 610 mm (24 in.) or less : Length 8,000 mm (314-15/16 in.)

Included Software	Roland CutStudio	Roland CutStudio Plug-in for Adobe® Illustrator®	Roland CutStudio Plug-in for CorelDRAW®
OS	Windows® 98SE/Me/2000/XP, Windows Vista® Home Premium or Business	Windows®, Mac OS	Windows®
Application Software		Adobe® Illustrator® 9/10/CS/CS2/CS3	CorelDRAW® 10/11/12/X3

Options					
Blades	ZEC-U1715	For cutting sandblast stencils for friction feed, maximum 1.00mm thickness, offset value 0.25mm, 5-pack	Roll hangers	HS-500	For GX-500, 1 set
	ZEC-U3017	For cutting sign vinyl in general plus cutting small letters or intricate designs, offset value 0.175mm, 3-pack		HS-400	For GX-400, 1 set
	ZEC-U5022	For cutting sign vinyl in general, offset value 0.25mm, 2-pack		HS-300	For GX-300, 1 set
	ZEC-U5025	For cutting thick, reflective and fluorescent vinyl, as well as sign vinyl in general, offset value 0.25mm, 5-pack			
Blade holders	XD-CH2	For sign vinyl in general as well as thicker material. Performs well for detailed cutting. Blade holder with blade extension adjuster, made of aluminum	Serial cable	XY-RS-34	3m (9.8ft)
	XD-CH3	For sign vinyl in general. Blade holder with blade extension adjuster, made of resin			

ISO 14001:2004 and ISO 9001:2000 Certified

Roland pursues both environmental protection and continuous quality improvement. Under the philosophy of preserving the environment and human health, Roland is actively working to abolish organic solvents in production, to reduce and recycle waste, to reduce power use, and to purchase recycled products. Roland constantly strives to provide the most highly reliable products available.



Roland reserves the right to make changes in specifications, materials or accessories without notice. Your actual output may vary. For optimum output quality, periodic maintenance to critical components may be required. Please contact your Roland dealer for details. No guarantee or warranty is implied other than expressly stated. Roland shall not be liable for any incidental or consequential damages, whether foreseeable or not, caused by defects in such products.

All trademarks are the property of their respective owners. Roland DG Corporation has licensed the MMP technology from the TPL Group.



AUTHORIZED DEALER:

Printed in Japan. RDG-416006099 09 JUL C-3 P-5

www.rolanddg.com